

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 910 964 A2**

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
28.04.1999 Bulletin 1999/17

(51) Int. Cl.⁶: **A43B 7/08**, **A43B 7/12**

(21) Application number: 98119626.4

(22) Date of filing: 16.10.1998

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 21.10.1997 IT PD970230

(71) Applicant:
Nottingham Holding B.V.
1077 Amsterdam (NL)


(72) Inventor:
Polegato Moretti, Mario
31035 Crocetta Del Montello (Treviso) (IT)

(74) Representative:
Modiano, Guido, Dr.-Ing. et al
Modiano & Associati SpA
Via Meravigli, 16
20123 Milano (IT)

(54) Vapor permeable shoe with improved transpiration action

(57) A vapor-permeable shoe which includes an upper (11), a tread (13) made of elastomer, shaped so as to form a plurality of domes (14) whose convexity is directed toward the ground, each dome having at least one minute through slit (15) which is normally closed due to the elasticity of the material and allows the out-flow of a mixture of air and water vapor formed inside the shoe when the compression applied by the sole of

the foot of a user generates an overpressure at the chambers formed internally by said domes, a vapor-permeable or perforated insole (17), and a waterproof and vapor-permeable protective membrane (18). The lower part of the upper, the tread and the membrane are perimetrically sealed in the regions where they join.



EP 0 910 964 A2

Description

[0001] The present invention relates to a vapor-permeable shoe.

[0002] It is known that a shoe, in order to be comfortable, must ensure correct exchange of heat and water vapor between the microclimate inside the shoe and the external microclimate. The exchanges of heat and vapor, however, must not compromise in any way the impermeability of the shoe to external humidity or water.

[0003] Currently commercially available shoes entrust the exchange of heat and water vapor substantially to the upper or to the sole. As regards the upper, shoes are commercially available which are perforated and/or provided with linings made of a vapor-permeable and waterproof material.

[0004] In some models, parts of the upper can be replaced with materials which are waterproof and at the same time vapor-permeable.

[0005] Another category of shoe instead entrusts transpiration to the sole, again by using layers of a waterproof and vapor-permeable material optionally associated with protective layers and fillers. These shoes, however, have not achieved an optimum exchange of heat and water vapor; accordingly, vapor-permeable shoes have been devised which are the subject of U.S. patent application 08/849,839, filed on June 6, 1997, in which the shoe is constituted by the following elements: a vapor-permeable upper, associated with a vapor-permeable or perforated lining; a tread made of perforated elastomer; a mid-sole, which comprises at least one membrane made of vapor-permeable waterproof material associated with a lower protective layer made of a material which is resistant to hydrolysis, is water-repellent, vapor-permeable or perforated; and includes a vapor-permeable or perforated insole and a vapor-permeable or perforated filler layer arranged between said insole and said membrane.

[0006] The lower part of the upper, the tread and the mid-sole with the membrane are perimetricaly sealed in the regions where they join.

[0007] Although this type of shoe solves many of the drawbacks observed in commercially available vapor-permeable shoes, it is not free from drawbacks, the main drawback being the fact that the vapor-permeable and waterproof membrane is not very strong from the mechanical point of view, is not protected in an optimum manner by the lower layer and can suffer damage due to interactions with blunt objects penetrating through the holes of the tread, which extend vertically with respect to the ground.

[0008] This type of shoe furthermore entails the drawback that the paths for the outflow of the air/water vapor mixture can clog at the sole, due to dirt wedging into the holes upon use.

[0009] The object of the present invention is to provide a vapor-permeable shoe which solves the drawbacks noted above of conventional shoes, particularly combin-

ing optimum heat and water vapor exchange, both through the upper and through the sole, with equally optimum protection of the components accommodated inside the sole.

5 [0010] Within the scope of this purpose, an object of the present invention is to provide a vapor-permeable shoe in which the sole is not subject to clogging of the transpiration paths.

10 [0011] Another object of the present invention is to provide a vapor-permeable shoe whose structure entails absolutely no restrictions in terms of styling and aesthetic research, allowing the greatest freedom of shape and production type.

15 [0012] Another object of the present invention is to provide a vapor-permeable shoe which is meant both for everyday use and for sports use.

[0013] Another object of the present invention is to provide a vapor-permeable shoe whose cost is competitive with respect to known vapor-permeable shoes.

20 [0014] A final object of the present invention is to provide a vapor-permeable shoe which can be manufactured with known technologies.

25 [0015] These objects and others which will become apparent hereinafter are achieved by a vapor-permeable shoe, comprising:

an upper;

a tread made of an elastomer, shaped so as to form a plurality of domes having a convexity directed toward the ground, each dome forming a chamber and having at least one minute slit which is normally closed due to the elasticity of the material and allows the outflow of the mixture of air and water vapor formed inside the shoe when compression applied by the sole of the foot of the user generates an overpressure at the chambers formed internally by said domes;

a vapor-permeable or perforated insole; and
a waterproof and vapor-permeable membrane interposed between said insole and said tread, the lower part of said upper, said tread and said membrane being perimetricaly sealed in the regions where they join.

45 [0016] Further characteristics and advantages of the present invention will become apparent from the following detailed description of two embodiments thereof, illustrated only by way of non-limitative example in the accompanying drawings, wherein:

50 Figure 1 is a perspective view of a first embodiment of a shoe according to the invention;

55 Figure 2 is a sectional view of the shoe of Figure 1; Figure 3 is a sectional view of a second embodiment of a shoe according to the invention.

[0017] With particular reference to Figures 1 and 2, a first embodiment of a vapor-permeable shoe according

to the invention is generally designated by reference numeral 10.

[0018] The shoe 10 comprises a vapor-permeable upper 11 which is associated with a sole 12. The upper 11 can be associated with a vapor-permeable or perforated lining, which is not shown in the Figures. In particular, the sole 12 has a tread 13 made of an elastomer, for example rubber, which is shaped so as to form a plurality of domes 14 having a convexity directed toward the ground.

[0019] Each one of the domes 14 has, substantially at a top portion thereof, a minute through slit 15 which is normally closed by virtue of the elasticity of the material and allows the outflow of the air/water vapor mixture that has formed inside the shoe when the compression of the sole of the foot generates an overpressure at the chambers 16 formed internally by the domes 14.

[0020] The shoe 10 also comprises an insole 17, which in this case is perforated but can also be vapor-permeable, and a waterproof and vapor-permeable membrane 18 of the type known commercially as Gore-Tex.

[0021] In particular, in this case the membrane 18 is associated with a lower protective layer 19 made of a material which is resistant to hydrolysis, and is water-repellent, vapor-permeable or perforated. The membrane 18, together with the layer 19, has an edge 20 which is embedded in the tread 13 so as to seal the joint. A seal is also provided between the upper 11 and the tread 13.

[0022] As regards operation, the overpressure generated inside the shoe vents air through the insole 17, the membrane 18 with the layer 19, and the minute slits 15 of the tread 13, which act as one-way valves by virtue of the particular dome-like configuration of the regions in which they are located. Accordingly, air flow occurs in a single direction.

[0023] Impermeability is ensured by the combined effect of the membrane 18 with the minute slits 15, which are normally closed.

[0024] With particular reference to Figure 3, a second embodiment of the vapor-permeable shoe according to the invention is generally designated by reference numeral 100.

[0025] In particular, the shoe 100 comprises an upper 101 (with an optional vapor-permeable or perforated lining, not shown), associated with a sole 102 which is in turn constituted by a tread 103 made of elastomer and shaped so as to form a plurality of domes 104 having a convexity directed toward the ground, each dome being provided with a minute through slit 105 which is normally closed by virtue of the elasticity of the material and allows the outflow of the mixture of air and water vapor, as described above.

[0026] The shoe 100 further comprises a vapor-permeable or perforated insole 106 and, between the insole and the tread 103, an intermediate element is provided which is generally designated by reference

numeral 107 and is described hereinafter. In particular, the intermediate element 107 is shaped so as to form, at the surface that is directed toward the insole 106, a plurality of first raised portions 108 which are suitable to support the insole and keep it spaced.

[0027] The intermediate element 107 is also shaped at the surface that is directed toward the tread 103 so as to form a plurality of second conical raised portions 109, each of which is inserted in a corresponding chamber 110 formed by the corresponding dome 104.

[0028] In particular, each one of the second raised portions 109 is suitable to close the opening of the corresponding chamber 110 when it is pushed and compressed by the sole of the foot, not shown, which rests thereon.

[0029] Through holes 111 are provided in the intermediate element 107 in order to allow the flow of air between the upper region and the lower region. The upper 101, the intermediate element 107 and the tread 103 are sealed in the regions where they join.

[0030] The intermediate element 107 provides outward mechanical pumping, through the minute slits 105, of the air that is in the regions between the second conical raised portions 109 and the domes 104, when the conical raised portions 109 perform alternating movements due to walking, particularly with downward movements after they have closed the corresponding chambers 110 and compressed the air contained therein. The flow of air is unidirectional and a good impermeability effect is ensured by the fact that the minute slits 105 are normally closed.

[0031] In a different embodiment, not shown in the Figures, it is possible to arrange between the intermediate element 107 and the insole 106 a membrane 18, optionally associated with a protective layer such as 19.

[0032] In practice it has been observed that the present invention has solved the intended aim and objects. In particular, it should be noted that the shoe according to the invention combines the need to provide optimum foot transpiration with the possibility to adequately protect the components inside the sole.

[0033] It should also be noted that the first embodiment combines the impermeability and vapor-permeability advantages of the membrane-fitted shoes cited in the introduction with the advantages of shoes in which the transfer of the air contained therein is performed mechanically with valves actuated by the compression of the foot during walking.

[0034] It should also be noted that the shoe according to the invention, in addition to being particularly tough, is substantially impermeable to external water vapor and water.

[0035] It is further noted that the structure of the shoe according to the invention does not compromise in any way research in terms of quality styling and aesthetic solutions.

[0036] It should also be noted that the constructive simplicity of the shoe according to the invention allows

the achievement of production costs which are competitive with respect to similar commercially available shoes.

[0037] The present invention is capable of numerous modifications and variations, all of which are within the scope of the inventive concept. 5

[0038] The constructive details discussed can be replaced with other technically equivalent elements. The materials and the dimensions may be any according to requirements. 10

[0039] The disclosures in Italian Patent Application No. PD97A000230 from which this application claims priority are incorporated herein by reference.

[0040] Where technical features mentioned in any claim are followed by reference signs, those reference signs have been included for the sole purpose of increasing the intelligibility of the claims and accordingly, such reference signs do not have any limiting effect on the interpretation of each element identified by way of example by such reference signs. 15 20

Claims

1. A vapor-permeable shoe characterized in that it comprises: 25


an upper;
a tread made of an elastomer, said tread being shaped so as to form a plurality of domes having a convexity directed toward the ground, each dome forming a chamber and having at least one minute through slit which is normally closed due to the elasticity of the material and allows outflow of a mixture of air and water vapor formed inside the shoe when compression applied by the sole of the foot of a user generates an overpressure at the chambers formed internally by said dome;
a vapor-permeable or perforated insole; and
a waterproof and vapor-permeable membrane interposed between said insole and said tread, the lower part of said upper, said tread and said membrane being perimetricaly sealed in regions where said tread and said membrane are joined. 30 35 40 45



2. The vapor-permeable shoe according to claim 1, characterized in that said upper is vapor-permeable and is associated with a vapor-permeable or perforated lining. 50
3. The vapor-permeable shoe according to claim 1, characterized in that it comprises a protective layer made of a material which is resistant to hydrolysis, is water-repellent, vapor-permeable or perforated and is directed toward the tread and which contacts said membrane. 55


4. The vapor-permeable shoe, characterized in that it comprises:

an upper;
a tread made of an elastomer, said tread being shaped so as to form a plurality of domes having a convexity directed toward the ground, each dome forming a chamber and having at least one minute through slit which is normally closed due to the elasticity of the material and allows the outflow of a mixture of air and water vapor formed inside the shoe when compression applied by the sole of the foot of the user generates an overpressure at the chambers formed internally by said domes;
a vapor-permeable or perforated insole;
a perforated intermediate element, said element being shaped so as to form, at a surface that is directed toward the tread, a plurality of conical raised portions, each of which is inserted in a corresponding chamber formed by a corresponding dome and closes said corresponding chamber when pushed and compressed by the sole of a foot of a wearer that rests thereon.

5. The vapor-permeable shoe according to claim 4, characterized in that said upper is vapor-permeable and is associated with a vapor-permeable or perforated lining.
6. The shoe according to claim 4, characterized in that said intermediate element has, at a surface directed toward the insole, a plurality of raised portions which are suitable to support said insole and keep it spaced from said domes.
7. The shoe according to claim 4, characterized in that a vapor-permeable and waterproof membrane is arranged between said intermediate element and said insole.
8. The shoe according to claim 7, characterized in that it comprises a lower protective layer made of a material which is resistant to hydrolysis, is water-repellent, vapor-permeable or perforated and which is directed toward the tread and contacts said membrane.







(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 910 964 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
06.12.2000 Bulletin 2000/49

(51) Int. Cl.⁷: **A43B 7/08, A43B 7/12**

(43) Date of publication A2:
28.04.1999 Bulletin 1999/17

(21) Application number: **98119626.4**

(22) Date of filing: **16.10.1998**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor:
**Polegato Moretti, Mario
31035 Crocetta Del Montello (Treviso) (IT)**


(30) Priority: **21.10.1997 IT PD970230**

(74) Representative:
**Modiano, Guido, Dr.-Ing. et al
Modiano & Associati SpA
Via Meravigli, 16
20123 Milano (IT)**

(71) Applicant:
**Nottingham Holding B.V.
1077 Amsterdam (NL)**

(54) Vapor permeable shoe with improved transpiration action

(57) A vapor-permeable shoe which includes an upper (11), a tread (13) made of elastomer, shaped so as to form a plurality of domes (14) whose convexity is directed toward the ground, each dome having at least one minute through slit (15) which is normally closed due to the elasticity of the material and allows the out-flow of a mixture of air and water vapor formed inside the shoe when the compression applied by the sole of the foot of a user generates an overpressure at the chambers formed internally by said domes, a vapor-permeable or perforated insole (17), and a waterproof and vapor-permeable protective membrane (18). The lower part of the upper, the tread and the membrane are perimetrically sealed in the regions where they join.



EP 0 910 964 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 11 9626

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP 0 728 424 A (GORE W L & ASS SRL) 28 August 1996 (1996-08-28) * the whole document *	1	A43B7/08 A43B7/12
A	WO 97 14326 A (POLEGATO MARIO ;NOTTINGTON HOLDING BV (NL)) 24 April 1997 (1997-04-24) * the whole document *	1	
A	US 4 071 963 A (FUKUOKA SADA0) 7 February 1978 (1978-02-07) * abstract; figures 1,6 *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			A43B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 18 October 2000	Examiner Scholvinck, T
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.02 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 11 9626

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-10-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0728424 A	28-08-1996	IT VI950018 U	21-08-1996
		JP 8252103 A	01-10-1996
		US 5746012 A	05-05-1998
WO 9714326 A	24-04-1997	IT PD950190 A	14-04-1997
		IT PD960126 A	17-11-1997
		AT 189103 T	15-02-2000
		AU 721719 B	13-07-2000
		AU 7288696 A	07-05-1997
		BG 102384 A	30-10-1998
		BR 9606686 A	23-12-1997
		CA 2234720 A	24-04-1997
		CN 1234725 A	10-11-1999
		CZ 9800969 A	15-07-1998
		DE 69606421 D	02-03-2000
		DE 69606421 T	21-09-2000
		EP 0858270 A	19-08-1998
		ES 2142620 T	16-04-2000
		HU 9900182 A	28-05-1999
		JP 11513582 T	24-11-1999
		NO 981565 A	06-04-1998
		NZ 320188 A	30-08-1999
		PL 326202 A	31-08-1998
		PT 858270 T	31-07-2000
		SI 858270 T	30-04-2000
		SK 45198 A	04-11-1998
		US 5983524 A	16-11-1999
US 4071963 A	07-02-1978	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)